

General Features	
Impedance: 50 ohm	Pressurisation: 300 hPa
Max.Insertion Loss: 0.1 dB	Materials: External Body: Brass;
VSWR (typical); 1.05	Inner Lines: Brass, Copper, Silver Plated Alu
Temperature Range: -40 +70°C	Insulators: Teflon; Finish: Painting RAL7001



Type	Fre. MHz	# out	Flange in	Flanges out	Power rating @ 600 MHz
DUB27700	470-860	2	EIA 7/8"	EIA 7/8"	2.8 kW
DUB21700	470-860	2	EIA 1-5/8"	EIA 7/8"	5.6 kW
DUB21100	470-860	2	EIA 1-5/8"	EIA 1-5/8"	6.6 kW
DUB23100	470-860	2	EIA 3-1/8"	EIA 1-5/8"	13.2 kW
DUB23300	470-860	2	EIA 3-1/8"	EIA 3-1/8"	20 kW
DUB24300	470-860	2	4-1/16"	EIA 3-1/8"	30 kW
DUB26300	470-860	2	EIA 6-1/8"	EIA 3-1/8"	40 kW
DUB26400	470-860	2	EIA 6-1/8"	4-1/16"	60 kW
DUB37700	470-860	3	EIA 7/8"	EIA 7/8"	2.8 kW
DUB31700	470-860	3	EIA 1-5/8"	EIA 7/8"	6.6 kW
DUB33100	470-860	3	EIA 3-1/8"	EIA 1-5/8"	20 kW
DUB34300	470-860	3	4-1/16"	EIA 3-1/8"	30 kW
DUB47700	470-860	4	EIA 7/8"	EIA 7/8"	2.8 kW
DUB41700	470-860	4	EIA 1-5/8"	EIA 7/8"	6.6 kW
DUB43700	470-860	4	EIA 3-1/8"	EIA 7/8"	11.2 kW
DUB43100	470-860	4	EIA 3-1/8"	EIA 1-5/8"	20 kW
DUB44100	470-860	4	4-1/16"	EIA 1-5/8"	26.4 kW
DUB44300	470-860	4	4-1/16"	EIA 3-1/8"	30 kW
DUB57700	470-860	5	EIA 7/8"	EIA 7/8"	2.8 kW
DUB51700	470-860	5	EIA 1-5/8"	EIA 7/8"	6.6 kW
DUB53700	470-860	5	EIA 3-1/8"	EIA 7/8"	20 kW
DUB67700	470-860	6	EIA 7/8"	EIA 7/8"	2.8 kW
DUB61700	470-860	6	EIA 1-5/8"	EIA 7/8"	6.6 kW
DUB63700	470-860	6	EIA 3-1/8"	EIA 7/8"	16.8 kW
DUB66300	470-860	6	EIA 6-1/8"	EIA 3-1/8"	69 kW
DUB87700	470-860	8	EIA 7/8"	EIA 7/8"	2.8 kW
DUB81700	470-860	8	EIA 1-5/8"	EIA 7/8"	6.6 kW
DUB83700	470-860	8	EIA 3-1/8"	EIA 7/8"	20 kW



Several models of UNBALANCED OUTPUT POWER dividers available.
Contact us for details