

General Features	
Impedance: 50 ohm	Pressurisation: 300 hPa
Max.Insertion Loss: 0.1 dB	Materials: External Body: Brass;
VSWR (typical); 1.05	Inner Lines: Brass, Copper, Silver Plated Alu
Temperature Range: -40 +70°C	Insulators: Teflon; Finish: Painting RAL7001

Type	Fre. MHz	# out	Flange in	Flanges out	Power rating @ 200MHz
DVB27700	174-240	2	EIA 7/8"	EIA 7/8"	5 kW
DVB21700	174-240	2	EIA 1-5/8"	EIA 7/8"	10 kW
DVB37700	174-240	3	EIA 7/8"	EIA 7/8"	5 kW
DVB31700	174-240	3	EIA 1-5/8"	EIA 7/8"	12 kW
DVB33100	174-240	3	EIA 3-1/8"	EIA 1-5/8"	35 kW
DVB47700	174-240	4	EIA 7/8"	EIA 7/8"	5 kW
DVB41700	174-240	4	EIA 1-5/8"	EIA 7/8"	12 kW
DVB43700	174-240	4	EIA 3-1/8"	EIA 7/8"	35 kW



Several models of UNBALANCED OUTPUT POWER dividers available.
Contact us for details