

FM Power Dividers

FM BAND

 Frequenza di utilizzo
Operative Frequency
 87.5 - 108 MHz

 Input Impedance 50 OHM
 VSWR (Typ.) ≤1.05

General data

Linee interne/ <i>Internal lines:</i>	Brass- Copper - Aluminum
Isolatori/ <i>Insulators:</i>	Teflon
Linee Esterne/ <i>External Lines:</i>	Brass-Copper
Finiture/ <i>Finishing:</i>	External-Painting Colour RAL7001/Polish Internal-Silver Plate

Modello <i>Model</i>	Flangia Ingresso <i>Input Size</i>	Nr. Uscite <i># output</i>	Flangia Uscita <i>Output Size</i>	Potenza (1) <i>Power (1)</i>	Ingombro Max mm (inches) <i>Max Dimensions mm (inches)</i>	Massa <i>Mass</i>
DFB37700	7/8" EIA	3	7/8" EIA	7.0 kW	1658 (65.3) x 177 (7.0) x 57 (2.2)	7.1 kg
DFB47700	7/8" EIA	4	7/8" EIA	7.0 kW	1658 (65.3) x 177 (7.0) x 57 (2.2)	7.5 kg
DFB21700	1-5/8" EIA	2	7/8" EIA	14.0 kW	1644 (64.7) x 187 (7.4) x 89 (3.5)	7.5 kg
DFB31700	1-5/8" EIA	3	7/8" EIA	15.0 kW	1644 (64.7) x 187 (7.4) x 89 (3.5)	8.1 kg
DFB41700	1-5/8" EIA	4	7/8" EIA	15.0 kW	1644 (64.7) x 187 (7.4) x 89 (3.5)	8.7 kg
DFB61700	1-5/8" EIA	6	7/8" EIA	15.0 kW	1644 (64.7) x 187 (7.4) x 138 (5.4)	9.9 kg
DFB81700	1-5/8" EIA	8	7/8" EIA	15.0 kW	1644 (64.7) x 187 (7.4) x 187 (7.4)	11.1 kg
DFB33700	3-1/8" EIA	3	7/8" EIA	21.0 kW	1692 (66.6) x 175 (6.9) x 175 (6.9)	23.0 kg
DFB43100	3-1/8" EIA	4	1-5/8" EIA	40.0 kW	1690 (66.5) x 289 (11.4) x 130 (5.1)	27.0 kg
DFS41700	1-5/8" EIA	4	7/8" EIA	(2)	1655 (65.2) x 201 (7.9) x 89 (3.5)	12.0 kg



(1): Potenza rms Massima supportabile a centro banda *Max rms supportable Input Power at Mid Band*

(2) DIVISORI SBILANCIATI, La potenza supportabile dipende dallo sbilanciamento. Chiedere dettagli sui tipi di sbilanciamenti disponibili.

(2) UNBALANCED POWER DIVIDER Max Power rating depends on output Unbalancment. Ask for available unbalancment ratio.